

## POWERSONIC 400 Series

CE RoHS

The Most Powerful Bench-top Ultrasonic Cleaner

POWERSONIC 410 (10liter)



Keypad

## POWERSONIC 500 Series

CE RoHS

The Most Powerful Bench-top Ultrasonic Cleaner

POWERSONIC 510 (10liter)



Keypad

### Features

- Built-in digital thermometer and timer to set optimum condition for cleaning
- Selectable use of ultrasonic power (3 steps : Low-1, Medium-2, High-3)
- Easy to read operation status on digital display
- Built-in drain valve unit
- Silicon rubber heater for durability and stability
- Built-in alarm function for operation stop
- Stainless steel tray (Optional)



### Specifications

| Model              | POWERSONIC 405                      | POWERSONIC 410       | POWERSONIC 420       |
|--------------------|-------------------------------------|----------------------|----------------------|
| Transducer         | Industrial BLT Type                 |                      |                      |
| Time Range         | 1~99 min [Digital]                  |                      |                      |
| Temp. Range        | Ambient~70 °C (Digital)             |                      |                      |
| Frequency          | 40 KHz                              |                      |                      |
| Housing Material   | ABS                                 |                      |                      |
| Bath Capacity      | 5.7 L                               | 10.7 L               | 20.7 L               |
| Bath Dimensions    | W300 x D155 x H150mm                | W300 x D240 x H150mm | W500 x D300 x H150mm |
| Overall Dimensions | W500 x D285 x H260mm                | W510 x D375 x H280mm | W720 x D450 x H280mm |
| Tray Dimensions    | W240 x D140 x H150mm                | W255 x D200 x H100mm | W500 x D300 x H150mm |
| Required Power     | 350 watt                            | 400 watt             | 700 watt             |
| Net Weight         | 7 kg                                | 9 kg                 | 14 kg                |
| Voltage            | Available from 100 to 240V, 50/60Hz |                      |                      |

### Features

- Backlit LCD screen (Furnishing all information)
- Selectable use of ultrasonic power (3 steps : Low-1, Medium-2, High-3)
- Easy to adjust time and temperature setting with number key
- Strong power and durability enhanced by built-in BLT transducer
- Manual function key for turning ON/OFF the heater
- Built-in alarm function for operation stop
- Stainless steel tray (Optional)

All information available on the "One digital LCD screen"

### Specifications

| Model              | POWERSONIC 505                      | POWERSONIC 510       | POWERSONIC 520       |
|--------------------|-------------------------------------|----------------------|----------------------|
| Display            | 70 x 40mm LCD Screen                |                      |                      |
| Transducer         | Industrial BLT Type                 |                      |                      |
| Time Range         | 1~99 min [Digital]                  |                      |                      |
| Temp. Range        | Ambient~70 °C (Digital)             |                      |                      |
| Frequency          | 40 KHz                              |                      |                      |
| Housing Material   | ABS                                 |                      |                      |
| Bath Capacity      | 5.7 L                               | 10.7 L               | 20.7 L               |
| Bath Dimensions    | W300 x D155 x H150mm                | W300 x D240 x H150mm | W500 x D300 x H150mm |
| Overall Dimensions | W500 x D285 x H260mm                | W510 x D375 x H280mm | W720 x D450 x H280mm |
| Tray Dimensions    | W240 x D140 x H150mm                | W255 x D200 x H100mm | W500 x D300 x H150mm |
| Required Power     | 350 watt                            | 400 watt             | 700 watt             |
| Net Weight         | 7 kg                                | 9 kg                 | 14 kg                |
| Voltage            | Available from 100 to 240V, 50/60Hz |                      |                      |