## **Funnel Shaker**



















### Powerful up-down reciprocal motion

#### Structural Functional Features

- · Vertical reciprocation at a maximum of 300 rpm.
- · 40 mm stroke length.
- · Adjustable shake tilt (0~20°) to achieve high mixing efficiency at low rpm.
- · Count-down timer. (up to 999 hours and 59 minutes)
- · 5kg on one side, 10kg in total.
- · Convenient holder height adjustment.
- · Stable device structure at high speeds.

#### Use Convenience Features

- · Digitally displays up-down reciprocal motion and it's easy to adjust speed with dial.
- Easy to detach separated funnel, maximizing convenience for repeat users.
- · Adjustable height of funnel holder makes it possible to mount funnels of various sizes. (up to 2L)
- 4 holders are provided as basic,
  10 holders can be mounted in maximum when it adds.
  (option, but the available mounted quantities are depends on the funnel size.)
- · Monitor via mobile app anytime, anywhere with LC Connected. (mobile monitoring system) (when purchased LC GreenBox)

#### Outstanding Safety

- · Alarms occur when there is a deviation between set rpm and actual rpm.
- $\cdot\,$  Over-current protection.
- $\cdot\,$  Optimized balance design to use in stable even when samples are installed at one side or tilted reciprocal motion.
- $\cdot\,$  Automatic restart in the event of sudden power loss.



RS-2 with Holders 4ea (standard), Holders 2ea (option)



Up to 5 holders may be installed on each side.



Tilt angle adjustment from 0 to 20° for maximum mixing efficiency.

#### **Specification**

| Model                                       | RS-2  |  |
|---|---|--|
| Shaking system                              |   |  |
| Motion type                                 | Vertical & Inclined reciprocating (0 ~ 20°) |  |
| Speed range (rpm)                           | Vertical 30 to 300 / Inclined 30 to 250     |  |
| Speed accuracy at 100rpm (± rpm)            | 1   |  |
| Amplitude, recip. stroke length (mm / inch) | 40 / 1.6                                    |  |
| Timer                                       | 999hr 59 min                                |  |
| Dimension                                   |   |  |
| Exterior (W x D x H, mm / inch)             | 600 x 460 x 470 / 23.6 x 18.1 x 18.5        |  |
| Minimum required space considering 20° tilt | 900 x 460 x 670 / 35.4 x 18.1 x 26.3        |  |
| Max. load per each side (kg / lbs)          | 5 / 11                                      |  |
| Net weight (kg / lbs)                       | 52 / 114.6                                  |  |
| Electrical data & Ordering No.              |   |  |
| 230V, 50/60Hz, A                            | 0.4   |  |
| Cat. No.                                    | AAH32025K                                   |  |
| 120V, 60Hz, A                               | 0.7   |  |
| Cat. No.                                    | AAH32023U                                   |  |

# Maximum number of installed funnels (per side)

| Funnel Capacity  | Round type | Cylindrical type |
|------------------|------------|------------------|
| Less than 500 mℓ | 3-5ea      | 3-5ea            |
| 500 mℓ           | 3ea        | 3ea              |
| 1L               | 3ea        | 3ea              |
| 2L               | 2ea        | 2ea              |

#### **Accessories**

| Cat. No.  | Description   |
|-----------|---------------|
| AAA32502  | Funnel holder |
| AAHQ1011K | LC GreenBox   |