



New Anemomaster™ LITE

Anemomaster™ Model 6006

Palm-size and feather-weight standard hot-wire anemometer

Anemomaster™ LITE is a compact and lightweight hot-wire anemometer unit. It offers research-grade accuracy at an affordable, industry competitive price. It has a detachable probe for easy replacement in the field without the need to recalibrate the unit. It comes in a dark metallic blue casing with anti-slip.

Applications

- HVAC Testing
- Facility Maintenance
- Critical Environment Certification
- IAQ Investigations



Features

- Weighs only 180g and is a very compact unit.
- Research quality at a contractor-friendly price.
- Extended 2 year warranty.
- Single switch operation in a comfortable ergonomic design
- The probe easily detaches from the main unit and can be replaced in the field.
- Includes 4 pcs. AA batteries, carrying case, and NIST Certificate.



Anemomaster™ LITE Specifications

Air Velocity:	Range	20 to 6000 FPM (0.01 to 20.0 m/s)
	Accuracy	+/- 5.0% of reading or 0.015 m/s whichever is greater
	Resolution	0.01 m/s (0.01 to 9.99 m/s), 0.1 m/s (10.0 to 20.0 m/s)
Temperature:	Range	-20 to 70°C +/- 1°
	Accuracy	0.5 °C
	Resolution	0.1 °C
Power Supply:		4 x AA batteries
Operation Range:	Main Unit	5 to 40 °C with no visible condensation -4 to 158 °C
	Probe	-20 to 70 °C with no visible condensation -10 to 50 °C
	Storage	with no visible condensation
Weight:		180 g
Dimensions:	Main Body	60 x 120 x 34 mm
	Probe	Probe Length: 205 mm
		Probe Diameter of Tip: 6.1 mm
Warranty:		2 years

Specifications are subject to change without notice.

Kanomax Japan, Inc.
2-1 Shimizu
Suita, Osaka 565-0805 JAPAN
TEL: +81-6-6877-0183
FAX: +81-6-6877-5570
E-mail: sales@kanomax.co.jp
URL: www.kanomax-usa.com

Distributed by:

